

APPLICATION ANWENDUNG/ APPLICATION / TOEPASSING/ APLICACIÓN / APPLICAZIONE	LANDSCAPING
PRODUCTION METHOD HERSTELLUNGSVERFAHREN/ MODE DE FABRICATION / PRODUCTIEPROCES PROCESODE FABRICACIÓN / PROCESSIDI FABBRICAZIONE	TUFTED
FIBRE FASER/ FIBRE/ VEZEL/ FIBRA/ FIBRA	PE + PP DTEX 6200
PILE HEIGHT POLHÖHE/ HAUTEURDU VELOURS/ POOLHOOGTE/ ALTURA DE LA PILA / ALTEZZO FELPA	±30 MM
TOTAL HEIGHT GESAMTHÖHE/ HAUTEURTOTALE/ TOTALE HOOGTE/ ALTURATOTAL / ALTEZZOTOTALE	±32 MM
PILE WEIGHT POLEINSATZGEWICHT / POIDS DU VELOURS/ POOLGEWICHT/ PESODE LA PILA / PESO FELPA	± 663 GR/M²
TOTAL WEIGHT GESAMTGEWICHT/ POIDS TOTAL / TOTAALGEWICHT/ PESOTOTAL / PESOTOTALE	± 1663 GR/M²
GAUGE TUFTTEILUNG/ JAUGE/ TUFTDELING/ GALGA/ SCARTAMENTO	3/8"
STITCHES (10 CM¹) STICHZAHL / NOMBREDE POINTS/ STEKENAANTAL / PUNTADAS / SERRAGGIOPUNTI	± 16 /10CM¹
STITCHES (M²) STICHZAHL / NOMBREDE POINTS/ STEKENAANTAL / PUNTADAS / SERRAGGIOPUNTI	± 16800 /M²
PRIMARY BACKING TRÄGER/ DOSSIERPRIMAIRE/ TUFTDOEK/ BACKING PRINCIPAL / SUPPORTOPRIMARIO	PP 135 GR/M²
SECONDARY BACKING RÜCKEN/ DOSSIER SECONDAIRE/ SECUNDAIREBACKING / BACKING SECUNDARIO/ SUP - PORTO SECONDARIO	LATEX ±865 GR/M²
WATER PERMEABILITY WASSERDURCHLASSIGKEIT/ PERMÉABILITÉ/ WATERDOORLATENDHEID/PERMEABILIDAD AL AGUA / PERMEABILITÀ ACQUA	60 L/MIN/M²
UV-WARRANTY NORTH EUROPE ABOVE PARIS, SOUTH EUROPEBELOWPARIS UV-GARANTIE/ GARANTIE UV / UV GARANTIE/ GARANTÍA UV / GARANZIA UV	EUROPE: 3 YEARS
ROLL WIDTH ROLLBREITE/ LARGEURDES ROULEAUX/ ROLBREEDTE/ ANCHO DEROLLO/ LARGHEZZA ROTOLO	2 M / 4 M
ROLL LENGTH ROLLÄNGE/ LONGUEURDES ROULEAUX/ ROLLENGTE/ LARGO DEL ROLLO/ LUNGHEZZA ROTOLO	±40 M
INFILL SAND FÜLLSAND / SABLE DE REMPLISSAGE/ INSTROOIZAND LA ARENA DE SÍLICE / SABBIA SILICEA	5-10 KG/M²

